


SPECIFICATION SHEET: S003

SYSTEM 1303 VEDETTE RANGE

THREE COMPARTMENT LOCKERS



Dimensions:

Height	Width	Depth	Nesting
1775 mm	225 mm	450 mm	- 2 3
1775 mm	300 mm	300 mm	1 2 3
1775 mm	300 mm	450 mm	1 2 3
1775 mm	380 mm	550 mm	1 2 -
1775 mm	380 mm	380 mm	1 2 -
1775 mm	380 mm	450 mm	1 2 -
1775 mm	450 mm	450 mm	1 2 -

Strength and Security with Style

Sturdy Construction	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength	Full length door stiffeners for extra door rigidity and two 'five knuckle' semi-concealed hinges.
Style	Attractive and functional locker design.
Colour	Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Compartment Size:	Compartment opening size 525 mm high (internal 555 mm), width and depth as above.
Nesting:	Lockers can be supplied as single units or nested in groups during the manufacturing process. All lockers are holed in back and sides to enable them to be bolted together into rows or back to back to suit your requirements. Note: When preparing locker room layouts allow approximately 4 mm extra for each nest for rivet heads at the sides of lockers in each row.
Construction:	Spot welded and pop riveted.
Material & Finish:	Mild steel powder coat (see Finish specification).
Door Frame Assembly:	Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section; top and bottom cross members which are designed to create door stops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.
Doors:	Doors are attached to the right hand side of door frame upright with two 'five knuckle' semi-concealed hinges per door. Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder. The inside of the door has a full length vertical 'stiffener' to provide greater rigidity. Two rubber buffers are fitted to the top and bottom corners of each door for quiet closure.
Bottom:	The bottom is formed as a 60 mm high plinth. All edges have return bends and the front and rear edges drilled for fitting to stands or stands with seat.
Locking:	Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Total Locker Service. As an optional extra, we can supply a door-mounted combination lock with master key override facility and user codes which can be reset.
Ventilation:	Ventilation is provided by a series of unique ventilation slots in the top cross member.

Paint Finish:	Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The component parts are then coated with polyester powder and stoved to ensure a hard paint finish is achieved.
Colour Range:	Standard locker frame powder colours are "Ice". Standard door stove enamelled colours are: "Ice", "Rockpool", "Smoke", "Nimbus", "Skye", "Kingfisher", "Royale", "Forest", "Cherry". The Total Locker Service general brochure illustrates these colours. Exact colour samples are available.
OPTIONAL EXTRAS:	The following can be supplied at an additional cost and, if included, will be specified in the quotation.
Combination Lock:	The standard cam lock or latch lock can be replaced with a door-mounted combination lock with master key over-ride facility and user codes which can be reset.
Perforation:	Most parts of the locker can be perforated with the unique perforation profile (please refer to Information Sheet I008).
Locker Numbering:	<ul style="list-style-type: none"> a) Number Label – Made of transparent vinyl, with a permanent, self-adhesive back. Numbers are printed in black and can comprise one to four digits. b) Number Plate – Made of laminated plastic, white numbers on black, numbers can comprise one to four digits. c) Number Discs – Laminated plastic 25 mm diameter, white numbers on black, numbers can comprise one to four digits. The disc is holed and a split key ring is provided.
Stands/Stand with Seats:	Lockers can be provided with either stands or stands with seats with or without adjustable feet. Please refer to Specification Sheet S015.
Sloping Tops:	Lockers can be manufactured with a sloping top (Gradient 1:3) ie, 450 mm deep unit increased height at rear 150 mm.
End Panels:	For aesthetic appearance and to protect row ends, specifically designed end panels are available.
Installation:	We offers a full installation service for its products.

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.