


# **SPECIFICATION SHEET**

## **SYSTEM 2000**

### **COIN OPERATED LOCKER**



#### **Nominal size of each locker:**

<b>Height</b>	<b>Width</b>	<b>Depth</b>
1800 mm	300 mm or 400mm	450 mm or 500mm

#### **Compartment height of each model:**

Full Length Compartment:	Base to shelf 1370 mm, shelf to top 308 mm
Two Compartment:	840 mm
Three Compartment (Unequal)	1 x 840 mm, 2 x 400 mm
Three Compartment (Equal)	3 x 545 mm
Four Compartment:	400 mm
Five Compartment:	308 mm
Six Compartment:	250 mm

**Half Height Unit:** 900 mm x 300/400 mm x 450/500 mm

Internal Height of Compartments:805 mm

### **Key Features**

Sturdy Construction	Door frame uprights constructed from heavy gauge extruded aluminium.
Door Strength	Manufactured from 10 mm thick compact grade laminate and supported by continuous aluminium hinge.
Door Security	The coin operated lock offers a 'Hook Bolt' design which provides engagement into the door frame for even greater security.
Style	Attractive and functional locker design. Extensive range of door colours and finishes available.

### **Detailed Product Specification**

Nesting:	All lockers will be supplied in singles for joining together on site. Note: When preparing locker room layouts allow approximately 2 mm extra for each locker in a row.
Method of Construction:	Pop riveted.
Body :	Aluminium with radiused internal corners.
Doors:	Attached to the door frame upright by a continuous aluminium extruded hinge. For health and safety all doors are sprung loaded
Door Materials:	Solid grade laminate providing high strength and aesthetic appeal. Please refer to the brochure. Exact colour samples are available.
Door Type:	Plant-on: this type of door creates a clean uninterrupted wall of colour.
Door Frame:	Heavy gauge extruded aluminium, profiled to allow smooth removal of bags.
Shelves:	Shelves are manufactured from high strength polymer and incorporate ventilation holes. Note: Full Length locker is fitted with a hat shelf.
Bottom:	Manufactured from high strength polymer and is fitted with floor fixing points.
Hooks:	The Single Compartment and Two Compartment lockers are supplied with a plastic moulded hook located on the right hand side of each compartment.
Locking:	Each door is fitted with a coin operated lock or Camlock, as required. When locked, the latch engages in the door frame upright providing increased security. Two patron keys supplied per lock; each key fitted with a key retaining pin complete with an engraved number disc made up of laminated plastic - white numbers on black. Disc is numbered to suit number on compartment door. Standard lock model: coin REFUND to accept one of the following: 1 x 20p, 1 x 50p, 1 x £1 coin, 1 x Euro or a token. Locks will be supplied set to choice of coin setting required by customer at time of original order. As an optional extra, we can supply the lock with a coin RETAIN facility. For improved management control, the lock can be supplied with removable lock barrels.
Cash Box:	For coin RETAIN operation, each lock is provided with one coin collection cash box, located on the inside of each door.

Management Key: Two control keys are supplied. Two cash box keys are supplied when coin RETAIN lock operation ordered by customer.

Numbering: Each door is complete with a laminate plastic number label. Label numbered to suit number on patron key number disc or wriststrap.

Ventilation: Ventilation holes in the tops, bottoms and shelves facilitate the flow of air through the locker.

Fixings: All necessary fixings are supplied so that lockers can be installed in accordance with our fixing specification, as detailed in System 2000 Installation Instructions

**OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.

Installation: We offer a professional installation service. When requested to install, this will be included within our quotation. If lockers are to be installed by others, instructions are supplied in leaflet reference I015 – System 2000 range – Installation Instructions.

Plinth: Whilst the locker can be mounted straight to the floor, we recommend lockers should be raised slightly above floor level. We can provide a 100 mm plinth manufactured from anodised aluminium or, alternatively, timber/concrete or other type of plinth can be provided by others.

Stands or Stands Frames are manufactured from anodised aluminium extrusion, self coloured. The seats are

With Seats: manufactured from hardwood, sourced from environmentally managed forests, finished with two coats catalysed lacquer, or, alternatively, extruded Polymer (colour: light grey NCS 5000).

Wall Mounting: System 2000 coin operated lockers can be wall mounted (depending upon fabric of proposed mounting wall).

End Panels: Locker row ends should be fitted with end panels. These can be offered as:  
a) Solid grade laminate material available in door colour.  
b) Anodised aluminium.  
c) End panels are available as singles to suit the side of single runs of lockers. Doubles are available in solid grade laminate only for lockers positioned back to back. Two single end panels are used for back to back lockers requiring anodised aluminium end panels. All necessary fixings supplied.

Wristbands: Several options are available – contact our Sales Department for details.

**After Sales Service: All of our products are supported by the Total Locker Service who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment.**

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

## Total Locker Service

Is a trading name of Safe Secure Locker Services Ltd

**Total Locker Service**  
Unit 3, Vision Centre  
5 Eastern Way  
Bury St Edmunds  
IP32 7AB  
Tel: (+44) 01284 718 733  
[sales@totallocker.co.uk](mailto:sales@totallocker.co.uk)